


The Driller's Choice




ROCK DRILL R405

LOW HEADROOM - HIGH POWER - MICROPILING - GEOTHERMAL APPLICATIONS









ROCK DRILL R405

The Rock Drill R405 is a low headroom micro piling drilling unit ideally suited for restricted access drilling sites and underground geothermal applications. Compatible with mud or air drilling setups. Standard features include breakout clamps, separate power unit, width adjustable crawler tracks, adjustable jack legs and a high torque drill head.

AVAILABLE OPTIONS

- Double Breakout Clamps.
- Safety Clamp System. Hands-free breakout.
- Auxiliary Winch. 42' rope / 1,470 lbs pull.
- Winch Extension Package. 2,000 lbs (907 kg) pull.
- Remote Controls. Tracks Only or Tracks, Rotation & Feed.*
- Dust Suppression System for DTH Hammer Drilling.
- Trip Wire Safety System. (European Spec).
- Mast Mounted Flood Lights.
- Mono Mud Pump. 150-180 gpm / 300-800 psi.*
- Longer Crawler Tracks.*

Key Features

Gate Clamps & Breakout Wrench with 8.8" ID (223 mm).

3-Position Manual Stabilizer Jack Legs.

Auxiliary Spool Control Function. (optional)

Separate Power Unit - Skid Mounted. (optional)


Width Adjustable Crawler Tracks. 34" - 52".




SPECIFICATIONS


Power & Hydraulics				
	IMPERIAL	METRIC		
SYSTEM PRESSURE	3,000 psi	206 bar		
MAX FLOW	33 gpm	125 lpm		
MAX PULLBACK	22,000 lbs	10,000 kg		
MAX PUSHDOWN	16,000 lbs	7,257 kg		
ENGINE POWER	83 hp	61 kW		
FUEL TANK	31 gal	117 ltr		
HYDRAULIC TANK	55 gal	189 ltr		
COOLING SYSTEM	Air cooled			


Rotary Heads JT-200 Series			
	IMPERIAL	METRIC	
MAX TORQUE	10,400 ft - Ilbs with JT205	14,000 Nm	
MAX SPEED	205 RPM with JT222-M		
THROUGH BORE	2 - 3/8"	60mm	
SPEEDS	2-speed variable		



TECHNICAL DRAWING







Dimensions & Weight				
	IMPERIAL	METRIC		
HEIGHT (DRILLING POSITION)	7' 3"	2,172 mm		
HEIGHT (TRANSPORT POSITION)	59"	1,499 mm		
LENGTH (DRILLING POSITION)	83"	2,108 mm		
MAST STROKE	4' 7"	1,397 mm		
WIDTH	34"	862 mm		
WEIGHT (RIG ONLY)*	3,300 lbs	1,500 kg		
TRACK ADJUSTABLE WIDTH	34" - 52"	863 - 1,320 mm		
TRACK LENGTH	40"	1,016 mm		

^{*} Dependant on options / Additional upgrades may be required





MINCON INC
603 Centre Ave NW, Roanoke,
VA 24016, USA
T. +1 540-344-9939
E. salesusa@mincon.com
W. mincon.com