

Typical: 0.15 0.40

FIRM (max characters no.=32)	BLADE No. ↓	ΔA (bar) <small>0.05-0.20</small>	ΔB (bar) <small>0.20-0.80</small>	⁽¹⁾ Δmm	Membrane Aspect ⁽²⁾
CUSTOMER ⁽³²⁾		Start			
JOB ⁽³²⁾		Z _E = ⁽³⁾			
SITE ⁽³²⁾		Z _E =			
REMARK ⁽³²⁾		Z _E =			
TEST NAME ⁽¹²⁾		DATE ⁽²⁰⁾		⁽¹⁾ Coaxiality error (L square) ⁽²⁾ Elastic, overinflated, wrinkled, snapping, scratched, etc. ⁽³⁾ Depth reached from extracted blade	
Absol. elev.(optional) _____ m Z _{water} (necess.) _____ m or <input type="checkbox"/> > Z _{final}					
Zero of gauge _____ bar γ _{top} _____ t/m ³ (default 1.75)					
<input type="checkbox"/> Rig <input type="checkbox"/> Penetrometer Diameter of rod behind the blade _____		TEST STOPPED → REFUSAL BECAUSE MEMBRANE † Z = Z _{prefixed}		<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> OPERATOR _____	

0	A	B	C	6				12				18				24			
2				2				2				2				2			
4				4				4				4				4			
6				6				6				6				6			
8				8				8				8				8			
1				7				13				19				25			
2				2				2				2				2			
4				4				4				4				4			
6				6				6				6				6			
8				8				8				8				8			
2				8				14				20				26			
2				2				2				2				2			
4				4				4				4				4			
6				6				6				6				6			
8				8				8				8				8			
3				9				15				21				27			
2				2				2				2				2			
4				4				4				4				4			
6				6				6				6				6			
8				8				8				8				8			
4				10				16				22				28			
2				2				2				2				2			
4				4				4				4				4			
6				6				6				6				6			
8				8				8				8				8			
5				11				17				23				29			
2				2				2				2				2			
4				4				4				4				4			
6				6				6				6				6			
8				8				8				8				8			