



PRODUCT SPECIFICATION SHEET

PREMIUM LUBE RDC PL-9501 **Heavy duty high performance grease. NLGI 2**

Hardrock Premium Lube: is a No.2 consistency grease, which is formulated to resist high temperature, water wash, fling off and wear. It contains a tackiness additive and has lubricating solids within its formulation.

Useable temperature range in continuous service is:
-30 to 150 degrees C

Application

General heavy loaded components, subject to arduous condition, hot, dusty or wet environment. A wide variety of applications such as, thread lubricant, general earth moving, heavy plant lubrication and sliding surfaces and in particular drill rod threads.

Application Methods

Applicable by pump over a wide range of temperatures and can also be applied by brush, spatula, lubricator or grease gun.

Appearance

Smooth grey in colour with a tacky consistency

Health and Safety

Information is available on relevant material safety data sheet.
Chemalert RMT 08 August 08

Performance Characteristics

KEY PROPERTIES

NLGI Grade	2
Type	Lithium Complex
Colour	Grey
Base Oil Viscosity	
CST @ 40C	185
CST @ 100C	41.6
Dropping Point C	190
Appearance	Smooth
Penetration @ 25C worked	270-290
Timken OK Load	32
Four Ball Weld Load Kg	800
Additives	Molybdenum Disulphide Copper Zinc Tackifier
Operating Temperature	-30-150C

Other Information

For further information on Hardrock products contact 0433 078685

All reasonable care has been taken to ensure that the information contained on this publication is accurate at the time of printing, however the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage etc.

Workshop: Unit 9/50 Banksia Rd Welshpool WA 6106 Postal: PO Box 644 Welshpool WA 6986

Tel: (08) 92584108 Fax: (08) 9258 6081 Mobile: 0433 078685

Email: hardrock@hardrockgrease.com.au

ABN 79 009 067 681