

SMALL BOLTER 99

Roof bolter for small to medium sections




SMALL BOLTER 99 for roof bolting and mechanized meshing, allows to efficiently and safely reinforce roof structures in underground mines, ideal for sections of 3 x 3 m up to 5.8 m of height.

Equipped with Bolting Turret T99 with two Montabert drifters, HC 50 for drilling and HC 28 for bolting and Magazine of bolts. It can install Split Set bolts, Rebar with resin or cement, Swellex, Hydrabolt and Python.

The boom mesh manipulator option allows mechanized meshing. All the entire combined operation can be performed safely for the operator.

Chassis for heavy duty, articulated 4WD, self-propelled with diesel engine and electrohydraulic system for drilling.

SPECIFICATIONS



DRIFTER

Drilling Feed

• Model	Montabert HC 50
• Percussion power	14 kW
• Percussion pressure	110 - 130 bar
• Frequency	62.5 Hz (3750 bpm)
• Rotation Speed	0 - 193 rpm
• Rotation torque	385 Nm
• Hole diameter	33 - 45 mm
• Air consumption (flushing)	7m ³ /min (8-10 bar)
• Air consumption (lubrication)	300 l/min (a 3 bar)
• Oil consumption (lubrication)	0.8 cc/min
• Water consumption	30-60 l/min (12-20 bar)
• Shank adapter	R32 female
• Weight	104 kg

Bolting Feed


• Model	Montabert HC 28
• Percussion power	9.5 kW
• Shank adapter	R32 female
• Weight	103 kg

BOLTING TURRET

• Model	T99
• Magazine of bolts capacity and plate (*)	10 bolts with 20 cm plate 12 bolts with 15 cm plate
• Double feed	RE 5000 Series
• Feed extension	340 mm
• Drifter advance	Hydraulic motor and chain
• Coupling mesh clamp feed drilling	
• Type of bolts	Split Set, Hydrabolt, Rebar, Swellex

Options:

Bolt (A)	Rod (B)	Turret length (C)
6' (1,829 mm)	7' (2,134 mm)	2,960 mm
7' (2,134 mm)	8' (2,438 mm)	3,383 mm



(*) Bolts from Ø46 or larger have another configuration

CARRIER

• Model	C44.8
• Diesel engine	Caterpillar C4.4 ACERT, Tier 3
• Power	106 kW @ 2200 rpm
• Exhaust catalyser	DOC (Diesel Oxidation Catalyst)
• Transmission	Hydrostatic
• Transmission pump	Sauer Danfoss
• Hydrostatic motor	Four MSE 18 motors
• Rear axle oscillating	± 8°
• Tramming speed:	
- Horizontal	Max. 9 km/h
- Positive ramp 15%	Max. 8.5 km/h
• Positioning pump	Parker
• Emergency and parking brakes	SAHR (Spring Applied Hydraulic Release)
	±40°
• Steering (articulated carrier)	10 x R15
• Tyres	2 extendable front, 2 rear
• Hydraulic jacks	FOPS / ROPS
• Canopy	15.8 gal / 60 l
• Fuel tank	2x12 V, 95 Ah
• Battery	24 VDC
• Electric system	8X, LED 28W, 9-32 VDC
• Tramming lights	SKF
• Centralized grease system	SKF
• Drilling lubrication system	
• Automatic fire suppression system	ANSUL, 4 nozzles
• Fire extinguisher	1x20 lb (PQS)

BOOM

• Model	Boom 14.3
• Boom extension	1000 mm
• Lift angle	+45° / -14°
• Swing angle	±35°
• Rotation	360°
• Hydraulic cylinders	



HYDRAULIC CONTROL SYSTEM

• Direct control valve	Parker KA-18
• Drilling control	DCS (Direct Control System)
• Percussion pump (compensated pressure)	Rexroth A10V071
• Gear pump	Parker
• Working pressure	180 - 200 bar
• Hydraulic oil tank	33 gal / 126 l
• Hydrostatic oil tank	22 gal / 86 l
• Hydraulic return filter	Parker, 10μ
• Hydraulic pressure filter	Parker, 10μ
• Hydraulic filter saturation indicator	Parker
• Low oil level indicator	Hydac
• Oil temperature indicator	Hydac

WATER AND AIR SYSTEM

• Electric compressor	CTN3
• Maximum capacity	1.65 m³/min
• Working pressure	8 bar
• Water pump and hydraulic motor	Grundfoss, CR5 - 9
• Maximum flow	6.9 m³/h (115 l/m)@3500rpm
• Minimum water inlet pressure	2 bar
• Bowman cooler	FG-120, 48.6 GPM, 20 bar
• Air tank	90 l

ELECTRIC SYSTEM

• Electric motor	55kW (75 HP)
• Voltage	380 - 440 VAC
	Option: 550 - 690 - 1000 VAC
• Frequency	50 - 60 Hz
• Starting method	Star - Triangle
• Option to 1000 VAC	Direct start
• Overload protection and ground fault	
• Percussion horometer	24V
• Phase sequence indicator	
• Battery charger	IN 32 VAC, 300W 13A
	OUT 28 VDC
• Electric transformer	1.5 kVA
• Working lights	2X, LED 50W, 9-32 VDC
• Electric cable reel	90 m
• Electric cable	3x1 AWG
• Degree of protection	IP 55

OPTIONS


• Diesel engine	Deutz BF4L914, Tier II, EPA II
	72.4 kW @ 2300 rpm
	FOPS/ROPS certifications
• A/C Enclosed Cabin	
• Tropical cooler for hot environments	
• Boom mesh manipulator	
• T99 turret (HC 50)	
	Drilling system HC 50
	Bolting system HC 50

Optional:

- Boom Mesh Manipulator



DIMENSIONS



Bolt	6'	7'
Length of rig (L)	9,730	9,866



Total Weight
13,345 kg

COVERAGE

Optimum work roof height
(**)

Bolt	Turret length (A)	Optimum (B)	Height Max. (C)
6' (blue)	2,960	4,765	5,473
7' (red)	3,383	5,190	5,898

(**) This is the optimal working height, where the equipment can install a row of bolts without moving the equipment.



TURNING RADIUS

