



Traxxon TR-EX 2000 Specifications

.5"
•

Attachment & Feed Assembly

Feed Beam_	Hi tensile formed steel
Drill Guides	
Drill Travel	Hydraulic chain feed
Feed Extension	
Steel Length	4.9m / 16' maximum length
Centralizer	Hydraulic with replaceable hardened bushings
Feed Swing	90 degree cylinder swing
Feed Dump	
Mounting	Quick attach bucket mount on boom stick
Storage	
Weight	2,400kg / 5,000lbs* without options or lugging

Controls & Hydraulics

Control System	Electronic, metering & adjustable
Control Mounting	Compact cab mounted & adjustable
Hydraulic Valves	Bosch Rexroth hydraulic & fully proportional
Valve Mounting	Protective steel housing on attachment
Hydraulic Supply	Excavator's hydraulics
Hydraulic Power	160lpm @ 180bar / 42gpm @ 2,650psi
Electric Power	24 Volt system
Connection	Single 24 wire cable & Amphenol connectors
Angle Indication	PQ indicator & control mounted display

Specifications — continued from page 1:

<u>Air</u>	Compressor

Compressor Type	_Self-contained, hydraulic driven
Air End Model	Rotorcomp EVO 9
Air End Type	Fully encapsulated screw compressor
Air Volume	300CFM Max. Operating
Air Pressure	
Cooling	Oil cooler with hydraulic driven fan
Cooling Control	
Drive	Hydraulic motor with gear coupling
Hydraulic Supply	
Hydraulic Power	110 - 160lpm @ 180 bar / 29 - 42gpm @ 2,650psi
Body	Skid mounted, steel housing & access hatches
<u>Options</u>	
Dust Collection	QMP 125 dust collector with swing away mount.
Steel Changer	Single steel automatic for 4.3m / 14' rods

Installation and Custom Design

Installation is available by our certified technicians at Traxxon's plant or your location.

Drifter Optional drills available, call for details

If you have a special requirement or unique application ask us about custom-built rock drill attachments. Traxxon Rock Drills has the expertise to design and manufacture custom equipment to meet your specialized needs.

Fine Print

Traxxon Rock Drills Ltd. has made every effort possible to ensure the equipment and specifications shown in this brochure are accurate based on the information at the time of printing. In some cases changes may be required due to availability of components, design changes and product improvements. Traxxon Rock Drills Ltd. reserves the right to make these changes without notice or obligation.